

Amendments In the Claims

Please add claim 25. Please amend claims 1, 13-16, 18-19, 21, and 24 as follows:

1. **(Presently Amended)** An apparatus comprising:
an optical connector interface to couple an optical network connector with a mounting surface; and
an electrical connector interface to couple an electrical network connector with said mounting surface,
wherein said optical connector interface and said electrical connector interface are vertically aligned with one another with respect to said mounting surface, and wherein said optical connector interface and said electrical connector interface are associated with a network element port **circuit**.
2. (Original) The apparatus of claim 1, wherein
said electrical connector interface comprises a registered jack 45 (RJ-45) interface.
3. (Original) The apparatus of claim 2, wherein
said optical connector interface comprises an interface of a small form factor pluggable (SFP) optical module.
4. (Original) The apparatus of claim 2, wherein
said optical connector interface comprises an interface of a gigabit interface converter (GBIC) optical module.
5. (Original) The apparatus of claim 2, further comprising:
an electrical isolation circuit coupled to said RJ-45 interface.
6. (Original) The apparatus of claim 5, wherein
said electrical isolation circuit comprises one or more magnetics components.

7. (Original) The apparatus of claim 2, wherein said optical connector interface and said electrical connector interface are associated with an auto-media detection network element port.
8. (Original) The apparatus of claim 2, further comprising: a visual indicator to indicate which of said optical connector interface and said electrical connector interface is active on said network element port.
9. (Original) The apparatus of claim 8, wherein said a visual indicator comprises at least one of a light emitting diode and a light pipe.
10. (Original) The apparatus of claim 2, wherein said electrical connector interface comprises an upper connector interface of said network element port, and wherein said optical connector interface comprises a lower connector interface of said network element port.
11. (Original) The apparatus of claim 2, further comprising: a first electromagnetic signal shield enclosing at least a portion of said optical connector interface; and a second electromagnetic signal shield enclosing at least a portion of said electrical connector interface.
12. (Original) The apparatus of claim 2, wherein said mounting surface comprises a printed circuit board.
13. **(Currently Amended)** An apparatus comprising: a network element port circuit; an optical connector interface; and an electrical connector interface; wherein said optical connector interface and said electrical connector interface are associated with said network element port circuit; and wherein said optical connector interface and said electrical connector interface are substantially adjacent to one another along a line defined by an intersection of

a connector-receiving plane of said network element port circuit and a connector-insertion plane of said network element port circuit.

14. (Currently Amended) The apparatus of claim 13[[,]] wherein said electrical connector interface comprises comprising:

~~wherein said electrical connector interface comprises~~ a registered jack 45 (RJ-45) interface.

15. (Currently Amended) The apparatus of claim 14[[,]] wherein said optical connector interface comprises:

an interface of a small form factor pluggable (SFP) optical module.

16. (Currently Amended) The apparatus of claim 14[[,]] wherein said optical connector interface comprises:

an interface of a gigabit interface converter (GBIC) optical module.

17. (Original) The apparatus of claim 14, further comprising:
an electrical isolation circuit coupled to said RJ-45 interface.

18. (Currently Amended) The apparatus of claim 17[[,]] wherein said electrical isolation circuit comprises:

one or more magnetics components.

19. (Currently Amended) The apparatus of claim 14[[,]] wherein said network element port comprises:

an auto-media detection network element port.

20. (Original) The apparatus of claim 14, further comprising:
a visual indicator to indicate which of said optical connector interface and said electrical connector interface is active on said network element port.

21. (Currently Amended) The apparatus of claim 20[[,]] wherein said a visual indicator comprises:

at least one of a light emitting diode and a light pipe.

22. (Original) The apparatus of claim 14,
wherein said electrical connector interface comprises an upper connector interface of
said network element port, and
wherein said optical connector interface comprises a lower connector interface of said
network element port.
23. (Original) The apparatus of claim 14, further comprising:
a first electromagnetic signal shield enclosing at least a portion of said optical
connector interface; and
a second electromagnetic signal shield enclosing at least a portion of said electrical
connector interface.
24. (Currently Amended) A method comprising:
coupling an optical connector interface associated with a network element port
circuit to a mounting surface; and
coupling an electrical connector interface associated with said network element port
circuit to said mounting surface such that said optical connector interface and
said electrical connector interface are vertically aligned with one another with
respect to said mounting surface, wherein
said electrical connector interface comprises a RJ-45 interface.
25. (New) The method of claim 5, wherein
said network element port circuit comprises said electrical isolation circuit.